

Serial Number: 10/051,478

Docket Number: 10012290-1

**IN THE CLAIMS:**

1. (Currently Amended) A serial bus expansion circuit, comprising:  
a bus distribution circuit selectively coupling a serial bus to one of a number of serial bus outputs;  
a distribution controller having a control output coupled to a control input of the bus distribution circuit; and  
a number of power-up pull resistors coupling each of the serial bus outputs to a power-up pull source, the power-up pull source including a state circuit that sequentially places a switch in a first state coupling a source voltage to the power-up pull resistors and in a second state coupling a common voltage to the power-up pull resistors in response to a system power-up condition.
2. (Original) The serial bus expansion circuit of claim 1, wherein a resistance of each of the power-up pull resistors is greater than a resistance of at least one external pull resistor coupled to the serial bus, thereby allowing an external pull source to override the power-up pull source.
3. (Original) The serial bus expansion circuit of claim 1, wherein the bus distribution circuit is a multiplexer.
4. (Canceled)
5. (Canceled)
6. (Canceled)

Serial Number: 10/051.478Docket Number: 10012290-1

7. (Original) The serial bus expansion circuit of claim 1, further comprising:

a serial bus input in the distribution controller configured for coupling to the serial bus; and

state circuitry in the distribution controller, the state circuitry generating a control signal that is applied to the control input of the bus distribution circuit in response to a selection message received via the serial bus, the selection message being addressed to the distribution controller.

8. (Original) The serial bus expansion circuit of claim 7, wherein the state circuitry generates the control signal in response to a selection payload in the selection message.

9. (Currently Amended) A serial bus expansion circuit, comprising: The serial bus expansion circuit of claim 7,

a bus distribution circuit selectively coupling a serial bus to one of a number of serial bus outputs;

a distribution controller having a control output coupled to a control input of the bus distribution circuit;

a number of power-up pull resistors coupling each of the serial bus outputs to a power-up pull source;

a serial bus input in the distribution controller configured for coupling to the serial bus;

state circuitry in the distribution controller, the state circuitry generating a control signal that is applied to the control input of the bus distribution circuit in response to a selection message received via the serial bus, the selection message being addressed to the distribution controller; and

wherein the state circuitry applies the control signal to the control input of the bus distribution circuit upon an occurrence of an acknowledge bit in the selection message.

Serial Number: 10/051,478Docket Number: 10012290-1

10. (Original) A system for serial bus expansion, comprising:  
means for selecting one of a number of devices to be coupled to a serial bus, wherein each of the devices is capable of communicating on the serial bus;  
means for selectively coupling the serial bus to one of the number of devices; and  
means for sequentially pulling a voltage potential of each of a number of serial bus inputs of the respective devices to a predefined source voltage potential and then to a predefined common voltage potential upon an occurrence of a system power-up condition.

11. (Original) The serial bus expansion circuit of claim 10, wherein the means for sequentially pulling the voltage potential of each of the number of serial bus inputs of the respective devices to the predefined source voltage potential and then to the predefined common voltage potential upon the occurrence of the system power-up condition further comprises a number of power-up pull resistors coupling each of the serial bus inputs to a power-up pull source.

12. (Original) The serial bus expansion circuit of claim 11, wherein the power-up pull source is a switch that toggles between a predefined voltage source and a predefined common voltage source.

13. (Original) The serial bus expansion circuit of claim 10, wherein the means for selecting one of the number of devices to be coupled to the serial bus further comprises means for generating a control signal based upon a selection message received via the serial bus and for applying the control signal to the means for selectively coupling the serial bus to one of the number of devices to direct a coupling of the one of the devices to the serial bus.

Serial Number: 10/051,478Docket Number: 10012290-1

14. (Original) The system of claim 13, wherein the means for applying the control signal to the means for selectively coupling the serial bus to one of the number of devices further comprises means for applying the control signal to the means for selectively coupling the serial bus to one of the number of devices during an occurrence of an acknowledge bit in the selection message.

15. (Currently Amended) A serial bus expansion method, comprising:  
providing a bus distribution circuit to selectively couple a serial bus to one of a number of serial bus outputs;  
determining a select one of the serial bus outputs to which the serial bus is to be coupled;  
controlling the bus distribution circuit to couple the serial bus to the select one of the serial bus outputs; and  
providing a number of power-up pull resistors that couple each of the serial bus outputs to a power-up pull source, the power-up pull source alternatively coupling each of the power-up pull resistors to a source voltage and a common voltage;  
coupling each of the power-up pull resistors to a source voltage in response to a system power-up condition; and  
subsequently coupling each of the power-up pull resistors to a common voltage.

16. (Original) The serial bus expansion method of claim 15, wherein the step of providing a number of power-up pull resistors that couple each of the serial bus outputs to a power-up pull source further comprises the step of providing for a resistance of each of the power-up pull resistors that is greater than a resistance of at least one external pull resistor coupled to the serial bus, thereby allowing an external pull source to override the power-up pull source

17. (Canceled)

Serial Number: 10/051,478Docket Number: 10012290-1

18. (Canceled)

19. (Currently Amended) A serial bus expansion method, comprising: The serial bus expansion method of claim 15,

providing a bus distribution circuit to selectively couple a serial bus to one of a number of serial bus outputs;

determining a select one of the serial bus outputs to which the serial bus is to be coupled;

controlling the bus distribution circuit to couple the serial bus to the select one of the serial bus outputs by wherein the step of controlling the bus distribution circuit to couple the serial bus to the select one of the serial bus outputs further comprises applying a control signal to a control input of the bus distribution circuit concurrently with an occurrence of an acknowledge bit in a selection message transmitted over the serial bus; and

providing a number of power-up pull resistors that couple each of the serial bus outputs to a power-up pull source.